

## Direct Mount Pressure Trapping Unloader

TRAPPED PRESSURE



### SPECIFICATIONS

Operating Pressure	4050 PSI
Maximum Pressure	4500 PSI
Maximum Flow	10.5 GPM
Temperature	195°F
Banjo Sizes:	Inlet 1/2" BSP-F Discharge 3/8" BSP-F
Port Sizes:	Inlet 1/2" BSP-F Discharge 3/8" BSP-F
Dimensions	8" x 4.6" x 1.7"
Weight	0.86 lb.
Material	Brass, Stainless Steel, Plastic, Buna-N

### PARTS LIST

No.	Part No.	Description	Kit Qty.
	Kit Y60161524	YU4050 Repair kit	*
1.	Y16210000	M 4 x 4 mm Set screw	1
2.	Y60172831	Lock nut	1
3.	Y60180651	M 8 piston	1
4.	Y60097824	YU4050 Seal set	* 1
5.	Y14744310	SS 11/32" ball	* 1
6.	Y60181331	Spring guide	1
7.	Y60097561	4.2 mm spring	1
8.	Y60172731	Brass cap	1
9.	Y60172684	YU4050 Black plast.knob	1
10.	Y60097331	Piston housing	1
11.	Y10307201	O-ring 1.78 x 20.35 mm	* 1
12.	Y60097924	VB280-350 val.pist.seal repair set	* 1
13.	Y60181031	Spacer	1
14.	Y10306801	O-ring 1.78 x 17.17 mm	* 1
15.	Y60180851	M 8 shutter	* 1
16.	Y60180951	Seat	* 1
17.	Y10306601	O-ring 1.78 x 15.6 mm	* 2
18.	Y14410000	3/8" washer	2
19.	Y60097135	Valve body	1
20.	Y60100731	3/8" Bsp Banjo bolt	1
21.	Y10318150	O-ring 2.62 x 17.2 mm	1
22.	Y14410100	1/2" washer	2
23.	Y60096135	1/2" Bsp brass manifold	1
24.	Y60100831	1/2" Bsp Banjo bolt	1
25.	Y60181131	3/8" Bsp F nipple	1
26.	Y60005351	Spring	1
27.	Y60005251	SS check valve	1
28.	Y10321308	O-ring 3 x 6 mm	1

