

YU5075K

Pressure Trapping Unloader



FEATURES

- Premium pressure compensated unloader for low spike pressures
- Adjustable max pressure settings
- Stainless steel internal components for maximum durability

SPECIFICATIONS

Operating Pressure	5100 psi
Maximum pressure	5650 psi
Maximum Flow	10.5 gpm
Temperature	195°F
Port Sizes: Inlet	3/8" Bsp-M
Discharge	3/8" Bsp-F
Bypass	1/2" Bsp-F
Dimensions	3.6" x 1.4" x 5.3"
Weight	2.0 lbs.
Materials	Brass, Stainless, Buna-N

PARTS LIST

Item	Kit	Part Number	Description	Qty.
Kit	*	Y60161524	Repair kit	1
1.		Y60181131	3/8 Bsp F nipple	1
2.	*	Y10306601	O-ring, 1.78 x 15.6 mm	2
3.		Y60005351	Spring	1
4.		Y60005251	S.S. check valve	1
5.	*	Y10321308	O-ring, 3 x 6 mm	1
6.		Y60172535	Valve body	1
7.	*	Y60180951	Seat	1
8.	*	Y60180851	M8 shutter	1
9.	*	Y10306801	O-ring, 1.78 x 17.17 mm	1
10.		Y60181031	Spacer	1
11.	*	Y60097924	Valve piston seal repair set	1
12.	*	Y10307201	O-ring, 1.78 x 20.35 mm	1
13.		Y60180531	Piston housing	1
14.		Y16210000	M 4 x 4 mm dowel	1
15.		Y60172831	Lock ring	1
16.	*	Y60097824	Piston seal repair set	1
17.		Y60180651	M 8 piston	1
18.	*	Y14744310	S.S. 11/32" ball	1
19.		Y60181331	Spring guide	1
20.		Y60181261	4.5 x 47 mm spring	1
21.		Y60172731	Brass cap	1
22.		Y60172984	Red plastic cap	1

